

# M-6311POE 15W POE IP Network Ceiling Speaker

**Product ID:** M-6311POE



## Short Description

POE supportable speaker  
Built-in 15W digital amplifier  
With MP3 decoding play

## Description

Support any audio sources play from the system center host machine;  
With MP3 decoding play function.

- ? 100/10Mbps, TCP/IP network transmission protocol adaptive
- ? Built-in 15W high efficiency digital amplifier with low power-consuming
- ? Built-in 15W 4? Hi-Fi speakers with high output sensitivity
- ? Output volume and display status can be controlled by system host

## Specification

Model		M-6311POE
AUX Input	Input sensitivity	300mV
	Frequency response	20Hz-20kHz
	Distortion	?0.3%

	S/N	≥75dB
MIC Input	Output sensitivity	4mV
	Frequency response	25Hz-16kHz
	Distortion	≤0.5%
	S/N	≥70dB
AUX Output	Rated output	1000mV
	Frequency response	25Hz-18kHz
	Distortion	≤0.5%
	S/N	≥75dB
USB/SD/Net/MP3	Frequency response	20Hz-20kHz
	Distortion	≤0.5%
	S/N	≥70dB
SD card storage		32GB
U disk storage		32GB
Rated power		15W
Power Supply		48V POE, IEEE802.3at standard 180-250V/50-60Hz
Product weight (Kg)		1.5
Dimension (LxWxH mm)		250x175x255

## Product Gallery

