

# L-VJM10A/EN Honeywell 10W Aluminum Unidirectional Projection Loudspeaker

**Product ID:** L-VJM10A/EN



## Short Description

Rated power: 10W

Meets outdoor requirements

EN54-24 certified, IP65 standard

## Description

L-VJM10A/EN is a high-performance 10W voice alarm unidirectional projection loudspeaker. It provides a broad frequency response range, low distortion and high sound pressure level for accurate and intelligible broadcast of evacuation messages and high-quality sound reproduction. It can be used in indoor, outdoor, dry, or wet applications, providing reliable operations over wide temperature and humidity ranges. Its low-profile, white color design blends easily with most interiors in locations such as hotels, conference rooms, cinemas, theme parks, factories and exhibitions. This voice alarm unidirectional projection loudspeaker complies with BS5839 part 8 and EN54 part 24.

? Intelligible voice and superior sound reproduction

? Ceiling or wall mount

? Meet virtually any outdoor requirements

- ? EN54-24 certified
- ? Complies with IP65 standard
- ? Available with or without capacitor (part number without “C”)

## Specification

Model	L-VJM10A/EN(C)	L-VJM10A/EN
Max power	20 W	
Rated power	10 W	
Power taps @ 100V	10 W / 5 W / 2.5 W / 1.25 W	
SPL at 10W/1W (100Hz-10KHz,1m)	98 dB / 89 dB	
SPL at 10W/1W (100Hz-10KHz,4m)	86 dB / 77dB	
Frequency response (-10 dB)	150 Hz - 20 KHz	
Rated input voltage	100 V / 70 V	
Rated impedance	1 K? / 2 K? / 4 K? / 8 K?	
Connection	Fire-resistant Cable	
Dimensions (DxL)	?140 mm x195 mm	
Weight	2.62 Kg	
Color	White (RAL9003)	
Material	Aluminum	
DC Blocking Capacitor	Yes (2.7uF)	No

## Product Gallery

