

EVAC-6006 EVAC Remote Paging Microphone

Product ID: EVAC-6006



Short Description

Support 12 zones paging
6 inputs & mic/line selection
6 zone selection

Description

Support 12 zones paging, totally support 32 microphones of loop connection in one system

6 inputs & mic/line selection button

6 zone selection buttons with three-colored indicator

Built-in monitor speaker

? Digital voice evacuation system remote paging microphone

? Each microphone contains 12 zone paging capacity

? System support 32 remote microphones by loop connection

? Microphone come with AC, DC, fault, Mic status and test indicators

? 6 inputs & mic/line selection buttons

? 6 zone selection button with three-colored indicators

? With reset/Cancel, All Call & Call button

? Two RJ45 ports for input and link output

? CAT5 or CAT6 cable communication up to 600 meters

? AC 230V and DC24V battery inputs

? Built-in monitor speaker

Specification

Model	EVAC-6006
Description	Voice Alarm Remote Paging Microphone
Power Consumption	3W
Zone Capacity	12 Zones
System Capacity	32 Remote microphones
Line Inputs	350mV, 10k?
Mic Input	5mV, 600?
Frequency Response	80Hz~16kHz
THD	<1% at RMS,1KHz
S/N Ratio	>70dB
Operating Temp	-20? to +70?
Power Supply	DC24V, ±20%
Humidity	<95% no condensation
Dimension (mm)	256(W)×149(H)×52(D)
Weight (Kg)	1.5

Product Gallery

