

# H-2288C/H-2288D UHF Wireless Chairman/Delegate Meeting Micorphone

**Product ID:** H-2288C/H-2288D



## **Short Description**

LCD display microphone ID, battery level, microphone state, control channel  
Equipped with microphone on/off key and indicator  
Chairman mic can turn on at any time

## **Description**

### **Chairman/Delegate Microphone**

- ? Portable table moving and microphone pipe can be pull out. Extended pipe option
- ? Electric capacity type microphone, euipped with windshield cover
- ? LCD display microphone ID, battery level, microphone state, control channel, etc.
- ? Equipped with microphone on/off key and indicator
- ? Equipped with 3 function keys to set microphone ID, control channel, volume level and battery status
- ? Microphone will shut off the power or in standby if receiver powered off

**Apart from above functions, the Chairman Microphone also has below functions**

- ? Chairman microphone can turn on at any time
- ? One system can support up to 16 units of chairman microphone

? Priority function: chairman can turn off delegate microphone by clear key any time

? Chairman only mode: delegate microphone can not be turned on again after chairman microphone press priority button. Chairman need quite this mode first, and then delegate microphone can be turned on again

## Specification

Item		Parameter
Audio channel	Transmission method	UHF wireless (one way)
	Audio channel	5 (1 chairman, 4 delegate)
	Carrying frequency	500MHz-950MHz
	Modulation method	FM
	Maximum modulation	60KHz
	Radiant power	?+9dBm
	Frequency deviation	<0.002
	S/N ratio	>85dB
	T.H.D.	<0.8%
	Frequency response	50Hz-15Hz
Data control channel	Transmission method	Wireless (two way)
	Data channel	16
	Frequency range	422.4MHz ~ 438.4MHz
	Modulation method	FSK
	Receiving sensitivity	-100dBm
	Transmission consumption	?6dBm
	Communication rate	100KBPS
	Frequency deviation	<0.002
System	Power supply	DC3.7~4.5V
	Signal covering range	Radius 60 meters
	Consumption rating	Standby: ?360mW Speaking: ?630mW
	Operating temperature range	-10-40 degree
	Dimension (mm)	170x58x120
	Net weight (Kg)	0.7

## Product Gallery

