LY International Electronics Co., Ltd - Room 1206 Aoyuan Jinsha Plaza Business Building, No. 26 Jinlong Road Nansha District, Guangzhou China, 511458
Phone: +86-20-39390663 - Email: sales@lyintl.com

H-3388C/H-3388D UHF Wireless Chaiman/Delegate Meeting Micorphone

Product ID: H-3388C/H-3388D



Short Description
LCD display microphone ID, battery level, microphone state, control channel
Equipped with microphone on/off key and indicator
Chairman mic can turn on at any time

Description
Chairman/Delegate Microphone

? Portable table moving and microphone pipe can be pull out. Extended pipe option
? Electric capacity type microphone, euipped with windshield cover
? LCD display microphone ID, battery level, microphone state, control channel, etc.
? Equipped with microphone on/off key and indicator
? Equipped with 3 function keys to set microphone ID, control channel, volume level and battery status
? Microphone will shut off the power or in standby if receiver powered off

Apart from above functions, the Chairman Microphone also has below functions

? Chairman microphone canturn on at any time
? One system can support up to 16 units of chairman microphone

? Priority function: chairman can turn off delegate microphone by clear key any time
? Chairman only mode: delegate microphone can not be turned on again after chairman microphone press priority button. Chairman need quite this mode first, and then delegate microphone can be turned on again

Specification

Item		Parameter
Audio channel	Transmission method	UHF wireless (one way)
	Audio channel	5 (1 chairman, 4 delegate)
	Carrying frequency	740MHz-790MHz 610MHz-659.75MHz
	Modulation method	FM
	Maximum modulation	60KHz
	Radiant power	?+9dBm
	Frequency deviation	<0.002
	S/N ratio	>85dB
	T.H.D.	<0.8%
	Frequency response	50Hz-15Hz
Data control channel	Transmission method	Wireless (two way)
	Data channel	16
	Frequency range	422.4MHz ~ 438.4MHz
	Modulation method	FSK
	Receiving sensitivity	-100dBM
	Transmission consumption	?6dBm
	Communication rate	100KBPS
	Frequency deviation	<0.002
System	Power supply	DC3.7~4.5V
	Signal covering range	Radius 60 meters
	Consumption rating	Standby: ?360mW Speaking: ?630mW
	Operating temperature range	-10-40 degree
	Dimension (mm)	170x58x120
	Net weight (Kg)	0.7

Product Gallery



