

# H-8610C/H-8610D Infrared Wireless Conference System Microphone

**Product ID:** H-8610C/H-8610D



## Short Description

Support discussion, voting and video camera auto-track  
Chairman unit priority function

## Description

? Portable table moving and microphone pipe can be pull out. Extended pipe option

? Electric capacity type microphone, equipped with windshield cover

? LCD color red/blue (option)

? LCD display microphone ID, signal level, battery level, microphone state, control channel, etc.

? Equipped with microphone on/off key and indicator

? Equipped with 5 function keys to set microphone ID, control channel, LCD contrast and light time

? Auto-close: Microphone will turn off automatically if there is no action of this

microphone in 99 seconds

? Microphone will shut off the power in 60 seconds to save battery power if system communication is error

? LCD will display 'IR Signal Weak' if the IR signal is weak when microphone working

**Including the functions of the delegate unit, chairman unit has other following functions:**

? Chairman microphone can turn on any time

? In one system microphone just support one chairman microphone and the ID number should be 1

? Priority function: chairman can turn off delegate microphone any time

? Chairman only mode: Delegate microphone can not be turned on again after chairman microphone press priority button. The chairman need quit this mode first, and then delegate microphone can be turned on again.

**Specification**

Description	Item	Parameter
Audio channel	Transmission Method	Wireless infrared
	Audio Channel	4
	Carrier Frequency Band	6MHz-8MHz
	Modulation Method	FM
	Infrared Radiator Consumption	±10dBm
	Mic Sensitivity	-44dB±2dB
	Frequency Response	100Hz-10KHz
	S/N Ratio	>70dB
	T.H.D.	<0.5%
	Reference Sound Receiving	10-30cm
Data control channel	Transmission Method	Wireless
	Date Channel	5
	Frequency Range	915MHz-925MHz

System	Modulation Method	FSK
	Receiving Sensitivity	-85dBm
	Transmission Consumption	10dBm
	Communication Rate	100KBPS
	Battery	LIP battery 12V/4000MAH
	Consumption Rating	8W
	Operating Temperature Range	0-40 degree
	Length of Gooseneck (mm)	400 (optional)
	Dimension (LxWxH) (mm)	220x155x69
	Net Weight (Kg)	0.818 (with battery)

## Product Gallery

