H-6600 Digital Discussion Conference System

Product ID: H-6600

Short Description
Support discuss
Support up to 250 units microphone with power extension unit

Description
? Designed accordance to ISO and IEC914 standards

? Main unit can support 60 units delegate and chairman microphone, it could be extend to support 250 unit microphone with extension power unit

? Equipped with four groups of 8P-DIN interface for system connecting

? With port for telephone interface unit, telephone meeting is available with telephone coincidence

? Build-in monitor loudspeaker

? System support discuss mode: Free mode, FIFO mode (1-9 microphone unit), Limit mode (1-9 microphone unit)

? System working mode can display on LCD

? Support video camera auto-track with video processor H-8008

? Support voting with voting processor H-8000

? Connection:
1 pc 13m main cable with 8 PIN plug
8 PIN socket for system connection

Specification

Item	Parameter
Power Supply	AC110V/240V 50Hz/60Hz
Consumption Rating	350W
T.H.D.	<0.05%
S/N	>75dB
Frequency Response	100Hz-18KHz
Color	Black
Net Weight (Kg)	8.0
Audio Input	RCAx1, ?6.35x1
Audio Output	RCAx1, XLRx1
Output voltage	DC24V
Output Impedance	47K?
Data Communication	RJ45x1
System Connection	8-PIN DINx4
Dimension (mm)	480x360x85
Installation	2U rack 19 inch frame

Product Gallery

H-6600 System Connection Diagram