

H-6800 Touch Screen Digital Video Conference System

Product ID: H-6800



Short Description

Support discuss, video camera auto-track & voting
Support 50 units meeting microphone
TFT LCD touch screen control

Description

? Designed accordance to ISO and IEC914 standards

? Power consumption of main unit 450W, each unit can support 50 units meeting microphone (1 chairman microphone & 49 delegate microphone)

? Combing video and audio signal in one cable

? This system can work with computer or without computer

? Main unit and microphone can display videos from camera or external video devices

? Main unit has following features:

- 1) Manage the meeting with software, support double screen display
- 2) Voting function (yes,no abstain)

- 3) Electing function (single-ballot and multiple-ballot)
- 4) Mode score: audience response (100, 75, 50, 25, 0)
- 5) Video camera auto-track function
- 6) Chairman can set following discuss work mode: free mode, FIFO mode(1-9 microphone unit), Limit mode (1-9 microphone unit),etc.

? TFT LCD display panel with touch control function, touch screen on main unit and microphone

? Equipped with 2 group video input interface

? Five groups of terminal interconnection interface for microphone connection

? Build-in RS-232 interface for PC connection

? Build-in video processor, support video camera auto-track function

? Build-in speaker on main unit and microphone

? Connection ports:

- 1 aux input (RCA)
- 1 line output(RCA)
- 1 rec output (RCA)
- 1 master output (XLR)
- 2 DVD video inputs (RCA)
- 8 cameras (or domes) inputs (RCA)
- 2 auto-tracking cameras control
- 2 video output (BNC)
- 5 mic connectors
- 1 computer control connector (RS-232)

Specification

Item	Parameter
Power Supply	AC110V/240V 50Hz/60Hz
Consumption Rating	400W
T.H.D.	<0.05%
S/N	>75dB
Frequency Response	100Hz-18KHz
Color	Black
Audio Input	RCAX1
Audio Output	RCAX2, XLRx1

