

H-EV02 SD High Speed Dome Camera

Product ID: H-EV02



Short Description

Ceiling mount & desktop

Horizontal resolution: 460-53 TV line

Description

Ceiling mount & desktop

Horizontal resolution: 460-53 TV line

Specification

Item	Parameter
Image	1/4 Super HAD CCD 1/4 Ex-view CCD
Effective pixels	440000 to 470000 pixels
Horizontal resolution	460-53 TV line
Signal format	NTSC / PAL
Synchronization	Internal / External
Video output	CVBS: 1.0Vp-p/75?
Scanning frequency	H: 15.625KHz V: 50Hz
Lens	10X optical, 12X digital zoom
Minimum object distance	10mm

Viewing angle	4.1°(tele)-4.8°(wide) 2.2°-54.2° 2.5°-50°
Focus distance	F=4.1-73.8, F=1.4-3.0, F=3.5-91, F=1.6-3.8, F=3.4-122.4, F=1.6-4.5
Minimum illumination	SD100AP: 1Lux / SD100BP: 0.7Lux; SD100CP: 0.001Lux / WD100-18BP: 0.0011Lux; SD70BP: 0.7Lux / SD70CP: 0.001Lux / SD70-26P: 0.01Lux WS70-18P: 0.001Lux / WD70-36P: 0.01Lux
Gain	Auto/Manual
Focus	Auto/Manual
SNR	>50dB
Shutter	1/50s to 1/10000; 1/1s to 10000 Auto/Manual
Pan tilt	60° (Pan), 120° (Tilt)
Pan tilt speed	0.1°-180° (Pan), 0.1°-120° (Tilt)
Pan tilt mode	Auto / Manual
Pan tilt orientation	Auto / Manual
Analog output	VBS(BNC), Y/C, CVBS:1.0Vp-p/75?
Control interface	RS-232/485, VISCA, PELCO P/D
Baud rate	115200/9600/4800/2400bps
Preset number	128 presets
Power	AC110V-AC220V to DC12V/1.5A