Phone: +86-20-39390663 - Email: sales@lyintl.com

H-98A 200 Channel UHF True Diversity Wireless Microphone

Product ID: H-98A



Short Description

2-channel diversity receiver 200 programmed UHF channels

Frequency: UHF 740MHz~789.75MHz

Transmission range: 100m

Description

- ? 2 Channel diversity receiver wireless microphone system
- ? 200 programmed, compatible UHF frequencies within the bandwidth in 250KHz frequency steps
- ? Scan and ACT (automatic channel targeting) function for easy location of free frequencies at the process of a button, easy transmission to transmitter by infrared diode per channel
- ? Channel selection, setting and control is performed with a user-friendly, front-mounted jog wheel and multi-color LED display that can be ready from a wide range of angles with displays for AF level, reception quality, remaining battery capacity, frequency, group and channel

Specification System Specification:

Workding Frequency	UHF 740MHz~789.75MHz		
	UHF 610MHz~659.75MHz		
Modulation	FM		
Frequency Channel	200		
Switching Bandwidth	250KHz		
Dynamic Range	>100dB		
S/N Ratio	>105dB		
T.H.D.	?0.5%		
Frequency stability	±0.005%		
Max Deviation	45KHz		
Frequency Response	80Hz-18KHz(±3)		

Receiver Parameter:

Function principle	True diversity receiver (UHF)		
Medium Frequency	110MHz, 107MHz		
Antenna Connection	4xBNC/50?		
Sensitivity	12dBuV		
Sensitivity Adjustment Range	12~32dBuV		
Noise Rejection	>75dB		
Max Output Level	+10dBV		

Transmitter Parameter:

Antenna	Build-in		
RF Output	<10mW		
Noise Rejection	-60dB		
Transmission Range	100m		
Power Supply	2pcs AA batteries		
Battery Life	10 hours in normal power; 12 hours in low		
	power		