

H-P600 Dual Channel Professional Amplifier

Product ID: H-P600



Short Description

2-channel, parallel or bridged

Output power: 2*600W (8?)

Description

- ? 2-channel, parallel or bridged, mono operating modes for flexible application
- ? Independent limiters for each channel offer dependable protection against distortion
- ? Precise signal and clip LED indicators to monitor performance
- ? High-current toroidal transformer for absolute reliability and lowest noise emission
- ? Independent DC and thermal overheat protection on each channel automatically protects amplifier and speakers
- ? "Back-to front" ventilation system including air filler will automatically adjust fan speed for smooth operation
- ? Balanced XLR and 1/4" TRS inputs
- ? Professional connectors compatible to Speaker and "touch-proof" binding post

loudspeaker outputs enable secure operation

Specfication

Power supply		AC 220V 50~60Hz
Input sensitivity/Impedance		500mV/20K?
Output power	8?	2x600W
	4?	2x800W
	Bridge 8?	1500W
Frequency response		20Hz-20KHz
S/N		>90dB
T.H.D.		<0.05%
Channel cross-talk		<-70dB
Channel impedance		4~16?
Net weight (Kg)		18.5
Produce dimension (LxWxH)mm		430x430x188
Color		Black

Product Gallery

