

WS-A15/WS-A20/WS-A25 4"/5¼"/6.5" Active Wall Mount Speaker

Product ID: WS-A15/WS-A20/WS-A25



Short Description

Rated power: 2*15W or 2*20W or 2*25W

Line input: 8?

Woofer speaker: 4" or 5¼" or 6.5" paper cone

Tweeter: 1½"

Description

This active wall mounted speaker system consists 1 master active loudspeaker and 1 slave passive loudspeaker.

The main active loudspeaker "L" builds in 2-channel stereo digital Class-D amplifier, with Phoenix connector ready to connect the passive loudspeaker "R".

With 3.5mm Mic input jack.

This speaker system is suitable for AV applications such as meeting rooms, classrooms, multi-media rooms, restaurants, coffee bars, etc.

Specification

Model	WS-A15	WS-A20	WS-A25
Rated power	15Wx2@8 ohm	20W×2@8 ohm	25W×2@8 ohm
Input sensitivity	0.5V		
Speaker driver	Woofer 4" + tweeter 1½"	Woofer 5¼" + tweeter 1½"	Woofer 6.5" + tweeter 1½"
Amplifier	2-channel digital stereo amplifier (Class D)		
Audio inputs	100V line inputs via Phoenix connectors		
MIC. input	3.5mm MIC jack		
Indicators	LED indicators for POWER "L" loudspeaker & "R" loudspeaker		
Material	ABS enclosure, metal bracket & grille		
Finish	White & black available		
Frequency response	60Hz-18KHz/1W, ±0.5dB		
THD	20Hz-20KHz/1W, 0.05%		
Ratio of damping	>200@8 ohm/400Hz		
S/N	>95dB		
Protection	Over-temperature, overload		
Power	AC 110V-240V/50Hz-60Hz		
Dimension	215*170*150mm	242*182*162mm	284*215*190mm
Mounting method	"U" shaped bracket adjustable		
Net weight	4.3Kg (1 main + 1 sub)	4.9Kg (1 main + 1 sub)	6.8Kg (1 main + 1 sub)

Product Gallery



