

WS-BT15/WS-BT20/WS-BT25 4"/5.25"/6.5" Bluetooth Wall Mount Speaker

Product ID: WS-BT15/WS-BT20/WS-BT25



Short Description

Rated power: 2*15W or 2*20W or 2*25W

Line input: 8?

Woofer speaker driver: 4" or 5¼" or 6½"

Tweeter: 1½"

With Bluetooth input

Description

This active wall mounted speaker system consists 1 master active loudspeaker and 1 slave passive loudspeaker.

The main active loudspeaker "L" builds in 2-channel stereo digital Class-D amplifier, with Phoenix connector ready to connect the passive loudspeaker "R".

* With 3.5mm Mic input jack.

* With Bluetooth input.

* Rated power:

WS-BT15: 2*15W @8 ohm

WS-BT20: 2*20W @8 ohm

WS-BT25: 2*25W @8 ohm

This speaker system is suitable for AV applications such as meeting rooms, classrooms, multi-media rooms, restaurants, coffee bars, etc.

Specification

Model	WS-BT15	WS-BT20	WS-BT25
Rated power	2*15W@8 ohm	2*20W@8 ohm	2*25W@8 ohm
Input sensitivity	0.5V		
Speaker driver	4" woofer + 1½" tweeter	5¼" woofer + 1½" tweeter	6½" woofer + 1½" tweeter
Amplifier	2*15W Class D digital	2*20W Class D digital	2*25W Class D digital
Audio inputs	Phoenix connectors		
MIC. input	3.5mm MIC jack		
Indicators	LED indicators for POWER "L" loudspeaker & "R" loudspeaker		
Material	ABS enclosure, metal bracket & grille		
Finish	White & black available		
Frequency response	60Hz-18KHz/1W, ±0.5dB		
THD	20Hz-20KHz/1W, 0.05%		
Ratio of damping	>200@8 ohm/400Hz		
S/N	>95dB		
Protection	Over-temperature, overload		
Power	AC 110V-240V/50Hz-60Hz		
Dimension	215*170*150mm	242*182*162mm	284*215*190mm
Mounting method	"U" shaped bracket adjustable		
Net weight	4.3Kg (1 main + 1 passive)	4.9Kg (1 main + 1 passive)	6.8Kg (1 main + 1 passive)

Product Gallery



