

WS-525BT 5¼" 2*30W Bluetooth Wall Mount Speaker



Product ID: WS-525BT



Short Description

Rated power: 2*30W

Line input: 8?

Speaker driver: 5¼" paper + 1½" tweeter

With RCA and 6.3m Mic input

With Bluetooth input

Individual volume control

Description

This active wall mounted speaker system consists 1 master active loudspeaker and 1 slave passive loudspeaker.

The main active loudspeaker "L" builds in 2-channel 2*20W stereo digital Class-D amplifier, with Phoenix connector ready to connect the passive loudspeaker "R".

With 6.3mm Mic input jack, L&R unbalanced inputs via RCA connector.

With Bluetooth play function.

Individual volume controls for audio input & microphone input.

Treble and bass tone control.

This speaker system is suitable for AV applications such as meeting rooms, classrooms, multi-media rooms, restaurants, coffee bars, etc.

Specification

Model	WS-525BT
Rated power	30W×2@8 ohm
Input sensitivity	0.5V
Speaker driver	Woofer 5¼" + tweeter 1½"
Amplifier	2-channel digital stereo amplifier (Class D)
Audio inputs	100V line inputs via Phoenix connectors "L&R" of unbalanced inputs via RCA connectors
MIC. input	6.3mm MIC jack
Indicators	LED indicators for POWER "L" loudspeaker & "R" loudspeaker
Volume controls	Individual volume controls for audio input & microphone input
Tone controls	Treble ±10dB, bass ±10dB
Material	ABS enclosure, metal bracket & grille
Finish	White & black available
Frequency response	60Hz-18KHz/1W, ±0.5dB
THD	20Hz-20KHz/1W, 0.05%
Ratio of damping	>200@8 ohm/400Hz
S/N	>95dB
Protection	Over-temperature, overload
Power	AC 110V-240V/50Hz-60Hz
Dimension	162*242*182mm
Mounting method	"U" shaped bracket adjustable
Net weight	4.7Kg (main loudspeaker 2.5Kg, sub loudspeaker 2.2Kg)

Product Gallery



