

# CM12 6 Zone Remote Paging Microphone

**Product ID:** CM12



## Short Description

6 zone remote paging  
2 built-in bell signal  
RJ45 connector

## Description

CM12 is a multifunctional remote paging microphone, connected by CAT cable with main host, and between microphone and microphone.

Each microphone is able to control 6 partitions.

It is also possible to control any partition separately or to switch on and off any partition on one-key basis, showing a high extent of humanization.

Multistage expansion is supported.

- ? Level indication
- ? Up to 6 partitions under control
- ? 2 built-in bell signal
- ? Adjustable volume of microphone and bell

? RJ45 socket is used for connection between microphones, support cascading connection

### Specification

|                                      |  |
|--------------------------------------|--|
| Mic input sensitivity                | 10±2mV (unbalanced input)                          |
| Line input sensitivity               | 2±0.1V (balanced input)                            |
| Signal output                        | 2±0.1V (balanced output)                           |
| Frequency response                   | Mic: 100Hz~15kHz (±3dB)<br>Line: 20Hz~20kHz (±3dB) |
| Signal to noise ratio                | Mic input ?60dB<br>Line output ?70dB               |
| Dimension of equipment<br>(L×W×H mm) | 232×146×68   |
| Packing size (L×W×H mm)              | 282×200×264  |
| Net weight                           | 1.9kg  |
| Gross weight                         | 2.6kg  |