LY International Electronics Co., Ltd - Room 1206 Aoyuan Jinsha Plaza Business Building, No. 26 Jinlong Road Nansha District, Guangzhou China, 511458
Phone: +86-20-39390663 - Email: sales@lyintl.com

PA-9823TS Wireless PA System Multi-functional Host

Product ID: PA-9832TS



Short Description

Integrated with timer, MP3 player, FM tuner, data coding modulator, alarm, microphone and 4G mobile phone paging

Specification

Item		Parameter
Input	Ground input	DTMB, F(75?)
	Line input	DVB-C, F(75?)
	FM input	F (75?)
	ASI input	BNC (optional)
	IP input	100/1000Mbps?UDP??
	GPRS receive module	Support SMS and telephone remote emergency paging
	2 group AUX input	RCA
	Balanced audio input	XLR (optional)
	AES/EBU input	XLR (optional)
	RDS input	BNC (optional)
	USB input	USB connector
		Audio file format: MP3
	2 Mic input	6.35mm and 3.5mm

Output	ASI output	BNC (optional)	
	IP output	UDP prototal, 100/1000Mbps	
	AUX output	RCA	
	Monitoring speaker	3W	
	Monitiroing output	3.5mm	
	RDS/FM output	F (75?)	
	2 timing power supply	220V 5A	
Parameter	Receiving mode	Support DVB-C/DTMB/FM/IP	
	Receiving frequency range	DVB-C: 30MHz~999MHz DTMB: 30MHz~999MHz FM: 87MHz~108MHz	
	Frequency output range	87-108MHZ	
	RF signal input level	DVB-C: -80dBm~0dBm DTMB: -85dBm~0dBm FM: ?-50dBm	
	Audio coding	Decode	MPEG-1 Layer 2
		Frequency	48KHz
		????	24-bit
		??	64Kbps
System	LCD screen display, press key control		
	Chinese/English		
	Temperature	0~45?(working)?-20~80?(storage)	
	Power supply	AC 100~265V±10%?50/60Hz	
	Standby consumption	<35W	
Output power	Amplifier output	120W (100V)	

Product Gallery

