

H-2400C 2.4G Wireless Conference System Chairman Microphone

Product ID: H-2400C



Short Description

LCD display microphone ID, battery level, microphone state

Microphone touch on/off panel

Priority function

Description

? Wireless & portable table moving

? Electric capacity type microphone, equipped with windshield cover

? LCD display microphone ID, battery level, microphone status, control channel, etc.

? Microphone will shut off the power or in standby if receiver powered off.

? Chairman microphone can be turned on at any time.

? Priority function: chairman can turn off delegate microphones by clear key any time

? Chairman only mode: Delegate microphone can not be turned on again after chairman microphone press priority button. The chairman need quit this mode first, and then delegate microphone can be turned on again

Specification

| Items | | Parameters |
|----------------------|-----------------------------|-------------------------------------|
| Audio channel | Transmission method | 2.4G (one way) |
| | Audio channel | 4 (1 chairman, 3 delegate) |
| | Carrier frequency band | 2400MHz~2483MHz |
| | Modulation method | FM |
| | Maximum modulation | 60KHz |
| | Radiant power | ?+9dBm |
| | Frequency deviation | <0.002 |
| | Frequency response | 50Hz-15KHz |
| | S/N Ratio | >95dB |
| | T.H.D. | <0.8% |
| Data control channel | Transmission method | 2.4g (one-way) |
| | Data channel | 16 |
| | Frequency Range | 2400MHz ~ 2483MHz |
| | Modulation method | FM |
| | Receiving sensitivity | -100dBm |
| | Transmission consumption | ?6dBm |
| | Communication rate | 100KBPS |
| | Frequency deviation | <0.002 |
| System | Power supply | DC 3.7V |
| | Signal covering range | Radius 60 meters |
| | Consumption Rating | Standby: ?360mW Speaking: ?630mW |
| | Operating temperature range | -10-40 degree |
| | Dimensions | 170×58×120mm |
| | N.W | 0.7kg |