

FS-3520/FS-3640/FS-3850 Outdoor Waterproof Wall Mount Speaker

Product ID: FS-3520/FS-3640/FS-3850



Short Description

Rated power: 20W or 40W or 50W

Line input: 70V/100V/8Ω

Speaker driver: 5" or 6.5" or 8" +1"

Waterproof IP66

With optimal bass enhancement radiator

Description

FS-3520/FS-3640/FS-3850 Outdoor waterproof wall mount speaker redefined a new design trend for wall mount speakers market where Beauty, Durability, Performance and User Friendliness come as ONE CORE CONCEPT.

IP66 Waterproof

Perfect for Outdoors Application



This series speaker delivers impeccable acoustic enjoyment, clean and clear announcements can be used both for public address systems and home audio systems.



Unique rear covers not only helps to cover the Euroblock Connector and Bypass Selector (PA Transformer) in the rear of the speaker, it is also designed to merge seamlessly with the OBE Bass Radiator and the overall design of speakers giving it an extra touch of modern sophistication.

Exclusive OBE Technology

Optimal Bass Enhancement Radiator



Features:

- ? Commercial PA system 70V/100V/8? wall mounted speaker
- ? Exclusive optimal bass enhancement radiator technology
- ? IP66, all weather speaker for indoor and outdoor use
- ? Rated output power: 20W (5") /40W (6.5") / 50W (8")
- ? 5" or 6.5" or 8" woofer speaker driver and 1" tweeter
- ? Quick installation with water-proof brackets
- ? Fashionable appearance with extraordinary sound quality

Specification

Model	FS-3520	FS-3640	FS-3850
Woofer driver	5" Graphite cone rubber surround	6.5" Graphite cone rubber surround	8" Graphite cone rubber surround
Tweeter driver	1" silk soft dome	1" silk soft dome	1.1" silk soft dome
Frequency range	100Hz-20KHz	90Hz-20KHz	80Hz-20KHz
Power handing RMS (IEEE219)	20W	40W	50W
Power handing RMS (program)	40W	80W	80W
Sensitivity	85dB±3	86dB±3	87dB±3
Power taps	20/10/5/2.5W/0/8?	40/20/10/5W/0/8?	50/25/12.5/6.25W/0/8?
Impedance	8?		
Termination	Pluggable terminal blocks		
Attachment	Brackets		
Dimensions (HxWxDmm)	258x170x168	285x198x195	381x250x250
Housing material	ABS		
Certificate	IP66 waterproof		
Packing dimension (HxWxDcm)	36x49x27	38x54x31	49x67x39

Product Gallery





