

LS-D25T/LS-D26T 100V 2-way Frameless Coaxial In Ceiling Speaker

Product ID: LS-D25T/LS-D26T



Short Description

Rated power: 30W or 40W

Line input: 100V

Speaker driver: 5" or 6.5" woofer + ¾" tweeter

Frameless grille

Description

Fashion design **Frameless grille**.

This series indoor ceiling speaker is coming with 5" or 6.5" woofer speaker driver and a 0.75" tweeter driver, 100 input.

Rated power:

LS-D25: 30W/100V (5"+0.75")

LS-D26: 40W/100V (6.5"+0.75")

High-class ABS material.

Suitable for public address system background music and home theater audio system usage.

Specification

Model	LS-D25T	LS-D26T
Rated power	30W	40W
Max power	60W	80W
Impedance	8?	
Sensitivity (1m,1W)	90±3dB	90±3dB
Frequency response	120-16KHz	100-26KHz
Woofer speaker driver	5"	6.5"
Tweeter speaker driver	¾"	
Product dimension (mm)	210x87	245x95
Hole for mounting (mm)	190	232
Frame material	ABS	
Grille material	Powder coated Iron mesh	
Color	White (RAL9016)	
Product net weight (Kg)	1.2	1.67
Gross weight (Kg)	9.0 (6pcs)	12.0(Kg)
Packing dimension (cm)	54x27x34	60x30x38

Product Gallery



