# FS-6430/FS-6640/FS-6850 Outdoor All Weather Waterproof Wall Mount Speaker

**Product ID:** FS-6430/FS-6640/F-6850

Phone: +86-20-39390663 - Email: sales@lyintl.com



#### **Short Description**

Rated power: 30W/40W/50W

Line input: 70V/100V/8?

 $4\frac{1}{2}$ "/ $6\frac{1}{2}$ "/8" woofer + 1" silk soft dome

IP66 All weatherproof

#### **Description**

FS-6 series outdoor wall mount speakers are one of **LYINTL**'s very hot selling products, suitable for both indoor and outdoor usage, IP66 fully waterproof.

Sleek and elegant appearance design, robust and durable premium grade material, built with high quality audio components and parts.





## 3 Different Size:

4.5" + 1"

6.5" + 1"

8" + 1

Graphite Cone, rubber surround woofer
1" Soft silk dome tweeter

## $70V/100V/8\Omega$ input, wit more power taps



Wateproof cover design

# **Specification**

- ? Build-in 70V/100V transformer and 8? power taps
- ?  $1\times4\frac{1}{2}$ ",  $1\times6\frac{1}{2}$ " or 1x8" graphite woofer speaker driver and 1" soft silk dome tweeter
- ? Rated output power: 30W, 40W or 50W
- ? IP66 all weatherproof, suitable for indoor and outdoor use
- ? White and black color for option

FS-6 series is built with a 70V/100V transformder and also with 8? input, can be used both for background music system and professional audio system applications, such like home music system, schools, stores, hotels, train stains, etc.

### **Specification**

Model	FS-6430	FS-5640	FS-6850
-------	---------	---------	---------

Rated power	30W	40W	50W
Power taps	3.75/7.5/15/30W/0/8	5/10/20/40W/0/8?	6.25/12.5/25/50W/0/
	?		8?
Line input	70V/100V/8?		
Output SPL	86±3dB	89±3dB	90±3dB
Freq. response	75Hz~20KHz	57Hz~20KHz	56Hz~20KHz
Woofer speaker	4½"x1 Graphite	6½"x1 Graphite	8"x1 Graphite cone
	cone	cone	
Tweeter driver	1"x1 silk dome	1"x1 silk dome	1.1"x1 silk dome
Waterproof	IP66		
Dimension	232x155x148	288x195x185	360x245x235
(H*W*D) (mm)			
Net weight (Kg)	-	-	-
Gross weight (Kg)	-	-	-
Packing dimension	-	-	-
(L*W*H) (mm)			

# **Product Gallery**





















