FS-3430 30W Dual 4" 2-Way Indoor Surface Mount Wall Speaker



Short Description

Power handling (RMS): 30W

Impedance: 8?

4"x2 PP cone woofer + 1"x1 Silk tweeter

Description

FS-3430 indoor wall mount speakers are coming with very elegant and sleek housing design, build-in 2pcs 4" low frequency woofer speaker driver and 1pc 1" high frequency silk soft dome tweeter.

Power handing (RMS): 30W (60W program)

4" x 2 (100mm) Polypropylene cone woofer, rubber surround

1" x 1 (25mm) Silk soft dome tweeter

This speaker can be widely used in schools, gyms, squares, parks, train stations, airports, villas, supermarkets, shopping malls and other places where need high quality sound level.

Specification

Specification	_
Model	FS-3430
Power Handing (RMS)	30W (60W program)
Impedance	8?
Sensitivity	85dB
Frequency response	135Hz-20KHz
Woofer speaker (LF)	4"x2 (100 mm) polypropylene cone,
	rubber surround
Tweeter speaker (HF)	1" (25 mm) silk soft dome
Product dimension (mm)	348 x 218 x 201
Installation cut out (mm)	-
Frame material	ABS
Grille	-
Color	White / Black
Product net weight	-
Gross weight	-
Packing dimension (cm)	-

Product Gallery













