

LS-D25THS/LS-D26THS 5"/6.5" Coaxial Frameless In-Ceiling Speaker with Fireproof Dome

Product ID: LS-D25THS/LS-D26THS



Short Description

Rated power: 30W or 40W

Line input: 100V/70V/8V

Speaker driver: 5" or 6.5" woofer + ¾" tweeter

Frameless grille

Description

Fashion design **Frameless grille**.

This series indoor ceiling speaker is coming with 5" or 6.5" woofer speaker driver and a 0.75" tweeter driver, 100 input.

Power taps:

LS-D25THS: 1.75W/3.5W/7.5W/15W/30W/8V (5"+0.75")

LS-D26THS: 2.5W/5W/10W/20W/40W (6.5"+0.75")

High-class ABS material frame and metal fireproof dome.

Suitable for public address system background music and home theater audio system usage.

Specification

Model	LS-D25THS	LS-D26THS
Rated power	30W	40W
Max power	60W	80W
Power taps (100V)	3.5W/7.5W/15W/30/8?	5W/10W/20W/40W
Power taps (70V)	1.75W/3.5W/7.5W/15W/30W/8?	2.5W/5W/10W/20W/40W
Line input	100V/70V/8?	
Sensitivity (1m,1W)	90±3dB	92±3dB
Frequency response	120-16KHz	300-8KHz
Woofer speaker driver	5"	6.5"
Tweeter speaker driver	¾"	
Product dimension (mm)	210x180	245x225
Hole for mounting (mm)	190	232
Frame material	ABS	
Grille material	Powder coated Iron mesh	
Rear cover material	Steel	
Color	White & Black	
Product net weight (Kg)	2.2	2.9
Gross weight (Kg)	15.0 (6pcs)	7.5(2pcs)
Packing dimension (cm)	54x27x34	65x33x37

Product Gallery

